



Primera's LX500e Colour Label Printer

Save Time and Money by Printing Your Own Short-Run Colour Labels!

LX500e utilizes the latest in high-resolution inkjet technology to print brilliant full-colour product labels right in your office or production facility.

Key Features of LX500e:

- Optional built-in label cutter
- Small, compact size
- Prints up to 101,6mm (4") wide
- 4800 dpi full-colour printing









Technical Specifications

Print Method:	Inkjet
Print Resolutions:	4800 x 1200 dpi, 2400 x 1200 dpi, 600 x 600 dpi
Print Speed:	Up to 50.8 mm (2") per second
Ink Cartridges:	Colour (CMY)
Colours:	16.7 million
Print Width:	19 mm (0.75") to 101.6 mm (4")
Print Length:	19 mm (0.75") to 609.6 mm (24")
Media Width:	25.4 mm (1") to 108 mm (4.25")
Media Types:	Roll-fed pressure-sensitive labels, roll-fed tags, fan-fold labels or tags
Media Sensing:	Moveable see-through sensor for die-cut labels; Reflective for labels and tags with black stripe; Continuous label stock; Preprinted label stock.
Supply Roll:	127 mm (5") maximum diameter on 50.8 mm (2") core. Core has additional restrictions – see manual.
Ink Level Warning:	Calculates actual number of prints remaining based upon ink usage of graphics being printed (patent-pending)
Indicator Lights:	Power, Ink
Controls:	Pause, Load/Feed, Unload
Recommended Minimum System:	For PC: Pentium® IV computer or better, 512MB RAM, 5GB free hard drive space, USB 2.0 or USB 1.1 For Mac: 1 GHz Intel processor or higher, capable of running Mac OS X v10.9 or higher, 1GB RAM, one available USB port
Label Design Software:	NiceLabel® Free 2019 and Bartender Ultralite included. Can also be used with most other popular label design software programs.
Electrical Rating:	12VDC, 5.0A
Power Requirements:	100-240VAC, 50/60 Hz, 60 watts
Certifications:	UL, UL-C, CE
Weight:	3.2 kg (7.0 lbs.)
Dimensions:	264 mmW x 389 mmD x 180 mmH (closed), 442 mmH (open) (10.4"W x 15.3"D x 7.1"H (closed), 17.4" (open))
Options:	Ink Cartridge, Tri-Color #53374 LX500e #074274 LX500ec #074276 (with cutter)
Operating Systems:	Windows® 7/10+, Mac OS X 10.9 or higher
Included:	Label design software for Windows,
	4x3" DTM Paper High Gloss starter roll and starter tri-color cartridge.

LX500ec model, featuring a built-in guillotine cutter

The built-in cutter allows you to cut die-cut, reflective and continuous label stock and offers several cut options. You can choose between the cut modes:

- do not cut for usage with a rewinder,
- cut after no activity for cutting when the print job is finished,
- **cut after button press** for cutting when you choose to press the button,
- **cut after every label** for producing e.g. single price tags or ID cards,
- cut after x labels which gives you the opportunity to choose the number of labels that needs to stay in one row before cutting.



DTM Print GmbH Mainzer Strasse 131 65187 Wiesbaden Germany Telefon: +49 611 92777-0 Email: sales@dtm-print.eu http://dtm-print.eu

©2019 DTM Print GmbH. All rights reserved. All other trademarks are the property of their respective companies. Specifications are subject to change without notice. All data and company names used in sample prints are fictitious. Patents pending. Product warranty may be different in the United States, Asia Pacific and Latin America territories. 190130